

PRIMO®

PRODUCT DESCRIPTION

PRIMO® ATF-III is a multi-purpose fluid, formulated with the high quality virgin base stocks and premium additives. Specially designed for excellent oxidation stability and thermal resistance. Refer to the vehicle manual for fluid & maintenance recommendations. PRIMO® fluids are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Enhanced friction modification properties for smooth shifting & durability
- Resistance to oxidation
- Provides thermal resistance
- Anti-wear agents protect critical transmission parts
- Helps protect against rust & corrosion

TYPICAL TEST DATA

ASTM TEST NAME	Test Method	ATF-III
Kinematic Viscosity @ 100° C, cSt	D445	7.2
Kinematic Viscosity @ 40° C, cSt	D445	35.9
Viscosity Index	D2270	170
Flash Point °C / °F	D92	195 / 383
Pour Point °C / °F	D97	-47 / -52
Foaming Test	D892	< 50 / 0
Color	visual	Red or amber

Typical test data may vary. Minor variations, which do not affect performance, may occur.

TYPICAL APPLICATIONS

- Can be used in older transmissions where Dexron III fluid is recommended
- Suitable for use in power steering systems where the manufacturer recommends a Dexron III or Mercon fluid

SHIPPING & PACKAGING DATA

PACKAGE SIZE	UNIT WEIGHT	UNIT VOLUME CU.FT	PALLET QUANTITY	PALLET WEIGHT
Case 12/ QT (946 mL)	24.5	0.78	98	2445
Case 4/ GL (3.78L)	32.5	1.03	60	1995
Pail 5 GL (18.9L)	38.0	1.24	42	1640
Drum 55 GL (208 L)	428	10.52	4	1760
Tote 265 GL (1000 L)	1930	49.4	1	1930

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

