

PRIMO®

PRODUCT DESCRIPTION

PRIMO® Gold Performance Full Synthetic ATFs are formulated with the highest quality virgin base stocks and the latest additive technologies to deliver outstanding performance while protecting critical transmission parts. Refer to the vehicle manual for fluid & maintenance recommendations. PRIMO® fluids are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- 100% synthetic technology for greater performance and protection
- One fluid can be used in numerous global transmission applications
- Helps prevent build-up of varnish and sludge
- Excellent friction properties for smoother shifting
- Optimal resistance to oxidation under severe operating conditions
- Maximum resistance to thermal breakdown
- Outstanding anti-wear properties to protect critical transmission parts
- Compatible with conventional fluids

TYPICAL TEST DATA

ASTM TEST NAME	Test Method	Low Viscosity Multi Vehicle	High Viscosity Multi Vehicle	Dex VI	ZF 8 & 9 Speed
Kinematic Viscosity @ 100° C, cSt	D445	6.0	7.1	6.0	7.1
Kinematic Viscosity @ 40° C, cSt	D445	29.65	31.9	29.7	31.9
Viscosity Index	D2270	155	195	155	195
Flash Point °C / °F	D92	210 / 410	210 / 410	210 / 410	210 / 410
Pour Point °C / °F	D97	-50 / -58	-50 / -58	-50 / -58	-50 / -58
Brookfield Viscosity @ -40°C, cP	D2983	12,000	13,000	12,000	13,000
Color	visual	Red or amber	Red or amber	red	Red or amber

Typical test data may vary. Minor variations, which do not affect performance, may occur.

TYPICAL APPLICATIONS

- See individual application charts, provided to distributors on request
- Not recommended for use in DCT, CVT, Ford Type F, Ford Type G applications

SHIPPING & PACKAGING DATA

PACKAGE SIZE	UNIT WEIGHT	UNIT VOLUME CU.FT	PALLET QUANTITY	PALLET WEIGHT
Case 12/ QT (946 mL)	24.5	0.78	98	2445
Case 4/ GL (3.78L)	32.5	1.03	60	1995
Pail 5 GL (18.9L)	38.0	1.24	42	1640
Drum 55 GL (208 L)	428	10.52	4	1760
Tote 265 GL (1000 L)	1930	49.4	1	1930

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

