PRODUCT DESCRIPTION

PRIMO® Bronze Performance Gear Oils are formulated using high viscosity index paraffinic US virgin base oils and specialty additives. PRIMO® oils exceed the toughest US performance standards for hypoids in automotive axles operating in high or low speed, high torque conditions. Also for use in heavy loading, shock loading, and extreme pressure operations. Refer to the vehicle or equipment manual for fluid & maintenance recommendations. PRIMO® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Anti-scuff additives & friction modifiers protect critical parts and equipment
- Helps resist rust, oxidation, foaming and varnish
- Helps maintain lubricity in extreme pressure conditions
- Formulated with Limited Slip performance

TYPICAL TEST DATA

ASTM TEST NAME	Test Method	80W-90	85W-140
Kinematic Viscosity @ 100° C, cSt	D445	15.5	26.0
Kinematic Viscosity @ 40° C, cSt	D445	145.4	310.2
Viscosity Index	D2270	110	110
Flash Point °C / °F	D92	220 / 428	240 / 464
Pour Point °C / °F	D97	-31 / -23	-17 / -1
Specific Gravity @ 60°F	D4052	0.88	0.88
Brookfleid Viscosity, cSt	D2983	130,000 @ -26C	130,000 @ -12C
Color	D1500	3.5	3.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

TYPICAL APPLICATIONS

- API GL-5
- Passenger car, SUV, light & heavy duty truck, bus, van
- Construction, mining, quarry, agricultural equipment

SHIPPING & PACKAGING DATA

PACKAGE SIZE	UNIT WEIGHT	UNIT VOLUME CU.FT	PALLET QUANTITY	PALLET WEIGHT
Case 4/ GL	32.5	1.03	60	2025
Case 4/5QT	40.5	1.22	40	1735
Pail 5 GL	38.0	1.24	42	1640
Drum 55 GL	428	10.52	4	1760
Tote 265 GL	1930	49.4	1	1930

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

