

# PRIMO®

## PRODUCT DESCRIPTION

PRIMO® Gold Performance Full Synthetic Gear Oils are formulated with high viscosity index paraffinic US virgin base oils and specialty additive technologies to deliver outstanding performance while protecting critical equipment parts. PRIMO® oils exceed the toughest US performance standards for high or low speed, high torque conditions, plus heavy loading, shock loading, and extreme pressure operations. Refer to the vehicle or equipment manual for fluid & maintenance recommendations. PRIMO® oils are warranted against defect when used & stored properly.

## FEATURES & BENEFITS

- 100% synthetic technology for extended performance and protection
- High shear stability extends the life of gears, seals and bearings
- Formulated with Limited Slip performance
- Resistance to rust, oxidation, foaming and varnish
- Helps maintain lubricity in extreme pressure conditions

## TYPICAL TEST DATA

ASTM TEST NAME	Test Method	75W-90	80W-140
Kinematic Viscosity @ 100° C, cSt	D445	15.5	25.0
Kinematic Viscosity @ 40° C, cSt	D445	113.2	218.2
Viscosity Index	D2270	145	145
Flash Point °C / °F	D92	220 / 428	225 / 437
Pour Point °C / °F	D97	-47 / -52	-35 / -31
Specific Gravity @ 60°F	D4052	0.87	0.87
Brookfleid Viscosity, cSt	D2983	130,000 @ -40C	130,000 @ -26C
Color	D1500	2.5	2.5

*Typical test data may vary. Minor variations, which do not affect performance, may occur.*

## TYPICAL APPLICATIONS

- MACK GO-J, API GL-5, MT-1, SAE J2360, MIL-2105-E, MIL-2105-F
- Passenger car, SUV, light & heavy duty truck, bus, van
- Construction, mining, quarry, agricultural equipment

## SHIPPING & PACKAGING DATA

PACKAGE SIZE	UNIT WEIGHT	UNIT VOLUME CU.FT	PALLET QUANTITY	PALLET WEIGHT
Case 4/ GL	32.5	1.03	60	2025
Case 4/ 5QT	40.5	1.22	40	1735
Pail 5 GL	38.0	1.24	42	1640
Drum 55 GL	428	10.52	4	1760
Tote 265 GL	1930	49.4	1	1930

*HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*

