

PRIMO®

PRODUCT DESCRIPTION

PRIMO® Gold Performance Full Synthetic Oils are formulated with the highest quality virgin base oils and latest additive technologies to deliver outstanding performance while protecting critical engine parts. PRIMO® oils exceed the toughest US performance standards for API SN PLUS and ILSAC GF-5 (where applicable). Also meets performance requirements of *dexos1Gen2* where applicable. Refer to the vehicle manual for fluid & maintenance recommendations. PRIMO® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- 100% synthetic technology to extend drain intervals
- Ultimate protection against sludge & soot for peak engine performance
- Friction modifiers & enhanced additives reduce engine wear
- Helps maximize fuel economy

TYPICAL TEST DATA

ASTM TEST NAME	Test Method	0W-16	0W-20	5W-20	0W-30	5W-30	10W-30	0W-40
Kinematic Viscosity @ 100° C, cSt	D445	7.1	8.0	8.0	10.5	10.5	11.0	13.0
Kinematic Viscosity @ 40° C, cSt	D445	36.7	42.35	43.35	59.1	60.55	67.7	73.65
Viscosity Index	D2270	160	165	160	170	165	155	180
Flash Point °C / °F	D92	210 / 410	205 / 401	210 / 410	210 / 410	215 / 419	220 / 428	210 / 410
Pour Point °C / °F	D97	-47 / -52	-47 / -52	-43 / -45	-47 / -52	-43 / -45	-40 / -40	-47 / -52
Specific Gravity @ 60°F	D4052	0.86	0.86	0.87	0.86	0.87	0.87	0.86
NOACK Volatility, %	D5800	13	13	13	13	13	11	13
Color	D1500	2.5	2.5	2.5	2.5	2.5	2.5	2.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

TYPICAL APPLICATIONS

- All viscosities are formulated for use in gasoline fueled cars and light duty trucks
- Super Low Viscosity 0W-16 is specially formulated for use in Japanese vehicles where recommended
- Meets performance requirements of API:SN PLUS, ILSAC GF-5, GM-6094M, *dexos1Gen2* (where applicable)
- Formulated for use in most vehicles made in North America (Ford, GM, Chevy, Chrysler, Cadillac, Dodge, Jeep) and in Asia (Honda, Toyota, Hyundai, Nissan, Mazda, Kia, Daewoo, Suzuki, Mitsubishi, Daihatsu)

SHIPPING & PACKAGING DATA

PACKAGE SIZE	UNIT WEIGHT	UNIT VOLUME CU.FT	PALLET QUANTITY	PALLET WEIGHT
Case 12/ QT (946 mL)	24.5	0.78	98	2445
Case 4/ GL (3.78L)	32.5	1.03	60	1995
Pail 5 GL (18.9L)	38.0	1.24	42	1640
Drum 55 GL (208 L)	428	10.52	4	1760
Tote 265 GL (1000 L)	1930	49.4	1	1930

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

